


# TECHNICAL SPECIFICATION

## TEKWRITE DRY ERASE VINYL WALLCOVERING

---

<b>Product</b>	Tekwrite Write On
<b>Description</b>	Available in gloss white finish.
<b>Weight</b>	862 grammes per square metre
<b>Fire Rating</b>	Euroclass B / Class 0 and 1 to BS476 part 6 and 7
<b>Roll Width</b>	121.4cm
<b>Adhesive</b>	Tekfix VOV
<b>Hanging</b>	<b><i>Best results will be obtained when the hanging surface is mirror smooth.</i></b> Can be installed either vertically (use a plumb line) or horizontally (use a level line), <u>though horizontal is recommended.</u>

Although seams can be written over, we suggest keeping seams out the major writing and viewing areas (80-230cm from the floor). In this way we would recommend hanging a half-width strip at the top of the wall - cut left to right along the length of the material - followed by a full width strip in the middle of the wall followed by another half strip. PHONE US ON 020 7536 3300 IF THIS IS UNCLEAR.



Reverse every other strip regardless of vertical or horizontal installation method. Paste wall, ensuring edges are well pasted. Re-paste any areas if there is a delay in hanging. Use a rounded spatula, covered in a cloth to smooth the Tekwrite to the wall. Reverse hang each alternate length, overlap and double cut through with a sharp blade. Change blade for each length. Smooth from the middle to the outside edge. Be sure to remove excess adhesive. Do not stretch material to butt seams – slide the entire length. Be careful not to crease the Tekwrite material when handling. Do not puncture air bubbles and do not use metal or sharp objects (other than the cutting knife) on the surface when installing the material. Once installed, the Tekwrite surface should be thoroughly washed down with clean water before using for the first time.

<b>Maintenance</b>	Recommended pens, erasers and spray cleaner are available to purchase online at <a href="http://www.tektura.com">www.tektura.com</a> (See 24 hour delivery). Use Bic Dry Erase markers for best results. Remove writing with bristle eraser for longer lasting surface effectiveness. Alternatively use microfibre towel for cleaning. Press firmly when erasing, using a circular motion. Change erasers or towels once dirty. For daily cleaning, or as required, wash the surface with water and rinse thoroughly. Remove remaining marks with spray cleaner. Always rinse with water. Do not use abrasive cleaners. Chalkboard pens can also be used. Chalkboard pen writing can be removed with a damp microfibre towel.
--------------------	---

<b>Health &amp; Safety</b>	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
----------------------------	---

**Fire Fighting**

Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.

**Ecological**

This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

---

—  
**TEKTURA**  
WALLCOVERINGS

TEKTURA PLC, Suite 1.03 Harbour Island, 34 Harbour Exchange Square, London E14 9GE  
Tel 020 7536 3300 Fax 020 7536 3322