TECHNICAL SPECIFICATION FABRIC-BACKED VINYL WALLCOVERING

Product	Zen Garden
Description	Commercial quality vinyl wallcovering laminated onto a polycotton osnaburg backing. 10% recycled content.
Weight	450 grammes per square metre.
Roll Size	137cm x 27m
Fire Rating	Euroclass C / Class '0' and '1' to BS476
Adhesive	Generally Tekfix Plus, though depends on substrate. Tekfix VOV should used when installing around right angled corners.
Hanging	Care should be taken during installation in order to produce optimum result Apply adhesive to wall surface. Carefully smooth wallcovering onto wall surface using a spatula, allowing 5-10cm at top and bottom for trimming. Over lengths, and double cut through. Run seam roller up join to ensure evaluates and clean water. Rinse thoroughly. This design has a 45cm vertical repeat. not reverse hang alternate lengths.
Maintenance	Fabric-backed vinyls offer an easy-clean finish, and high resistance to know and scrapes. They are designed to withstand high traffic levels, and will tear easily. With regular cleaning they will retain their original appearance many years depending on area of use.
	Always carry out a trial in an inconspicuous area first, to ensure cleaning ag suitable. Clean with a mild non-soapy detergent with soft cloth, sponge or s bristle brush to prevent build up of dirt and staining. Avoid polishes a abrasive cleaning agents as they will cause build up of dirt in the surfa- texture, and can also damage metallic finishes. Avoid strong active solv cleaners as they can stain and damage the vinyl surface. Diluted bleach can used to wipe surface. Always clean from the skirting level upwards. Rir thoroughly with clean water. Individual stains should be removed as quickly possible. This wallcovering contains antimicrobials which guard against mild and bacterial growth.
Health & Safety	This product is classified as non-hazardous and therefore does not requany special handling. This product does not require special labelling.
Handling/Storage	Store at ambient temperatures away from heat source. Suitable lifting equipment may be required.
Fire Fighting	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
Ecological	This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor. EPD on request.

TEKTURA

TEKTURA Ltd, 34 Harbour Exchange Square, London E14 9GE Tel 020 7536 3300 info@tektura.com